

Six Upstream Models: Flow Rates and Applications (Product Line)

	Upstream™ 10, 75% UVT *, 1"	Upstream™ 10, 50% UVT, 1"	Upstream™ 15, 75% UVT, 1"	Upstream™ 15, 50% UVT, 1"	Upstream™ 30, 75% UVT, 1"	Upstream™ 30, 75% UVT, 1.5"
Max Flow Rate (US GPM)	10 US gpm, 38L/min, 2.3 m ³ /hr	10 US gpm, 38 L/min, 2.3 m ³ /hr	15 US gpm, 57 L/min, 3.4 m ³ /hr	15 US gpm, 57 L/min, 3.4 m ³ /hr	30 US gpm, 113 L/min, 6.7 m ³ /hr	30 US gpm, 113 L/min, 6.7 m ³ /hr
UV transmittance * (at 254nm - %UVT)	75%	50%	75%	50%	75%	75%
Inlet - Outlet Size	1"	1"	1"	1"	1"	1.5"
"Lamps" used	H13	Only one new LAMP SKU		H30	H30	H30
Model Number	10-75	10-50	15-75	15-50	30-75/1.0	30-75/1.5
Recommended Application, or Water Source	Drilled Deep Wells	Unprotected water sources: Surface Water - Lakes, Streams, Cisterns, Dug Wells.	Drilled Deep Wells	Unprotected water sources: Surface Water - Lakes, Streams, Cisterns, Dug Wells.	Drilled Deep Wells	Drilled Deep Wells

* Ultraviolet Transmittance (UVT) is a measure of the percentage of UV light that may pass through the water.